



Chemblend FFD0090

Masterbatch, mold release agent for Polyester

06/29/22

Appearance:

White Colored pellet

Description:

Masterbatch additive to be dosed at the press to improve lubricity and flow of polyester thermoplastics.

Technical Data:

Carrier Resin: Polyester

Properties:

- Handling and storage without risk
- Dust Free Dosage
- Direct Dosage (without predrying)
- Compatibility of components and decomposition products with Polyester resins
- No polymer degradation

Application:

- Injection additive

Recommended Use Levels:

- 0.5 – 2.0 %

Although all statements and information in this publication are believed to be accurate and reliable, they are presented gratis and for guidance only, and risks and liability for results obtained by use of the products or application of the suggestions described are assumed by the user. NO WARRANTIES OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH. Statements or suggestions concerning possible use of the products are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe any patent. The user should not assume that toxicity data and safety measures are indicated or that other measures may not be required.